



PVC Pipe Wrapping Tapes



Aluminium Foil Tapes



Foil Scrim Kraft Tapes



Aluglass Tapes



Foil Scrim Metalized PET Tapes







PVC Pipe Wrapping Tapes



Description

PVC pipe wrapping tape composed of soft film with rubber based PSA it is characterised by excellent insulation, good flame retardant properties and excellent resistant to low temperature.

Application

This is used a lot by underground pipe contractor to protect Iron & Steel pipe from corrosion, also used to protect PVC pipe from corrosion due to ultraviolet rays in above the ground installation. This tape is also used in oil field industry to wrap above and underground pipes prevent corrosion due to high methane levels in the soil around oil field.

Packing Construction

Thickness	Width	Length	Rolls/CTN	
0.13	2"	100ft	60	
0.13	2"	90ft	60	
0.16	2″	100ft	60	
0.16	2"	90ft	60	









Description

A dead soft malleable aluminium foil coated with an aggressive Acrylic & Hot melt adhesive. Superior quick stick at normal temperatures with superior performance at freezing.

Application & Feature

- Provide an excellent vapour barrier, as it conforms well to irregular surfaces.
- Create a heat shield, benefiting the appliance and automotive industries.
- Wrap copper refrigeration coils inside refrigerator walls.
- Mask sensitive components from damage during paint stripping, such as when commercial airplanes are sandblasted and repainted.

Packing Construction

Width	Length	Rolls/CTN
2"	30Yds	24
3"	30Yds	16
4"	30Yds	12

Foil Scrim Kraft Tapes



Description

FSK is a tridirectionally reinforced foil-scrim-kraft lamination, combined with a transparent high performance pressure sensitive adhesive, protected by an east release paper. Designed and crafted to provide durable and reliable high quality joints & seams sealing in HVAC duct work applications, enhancing the vapor barrier integrity.

Application

FSK is primarily used for bapor sealing where FSK is the basic insulation facing FSK tapes blends with the primary facing and gives a strong aesthetically pleasing appearance for the HVAC system. Another primary use is to seal longitudinal and butt joints of FSK faced pipe insulation

Packing Construction

Width	Length	Rolls/CTN
2″	30Yds	24
3″	30Yds	16
4"	30Yds	12



Aluglass Tapes



Description

Aluglass facing laminated with Fibre glass cloth coated with an aggressive synthetic Rubber, producer excellent reflection to heat and light.


Application

Wide range of applications in Construction industry, shield and Lamination for air conditioning ducting system in HVAC for duct sealing of pipes and roof insulation.

Packing Construction

Width	Length	Rolls/CTN	
2"	30Yds	24	
3"	30Yds	16	
Δ"	30Yds	12	
4	30 TUS	12	

Foil Scrim Metalized PET Tapes



Description

A foil facing metalised Polyester laminated with Fibre glass cloth coated with an aggressive hot melt adhesive. Superior quick stick at normal temperatures

Application

Wide range of applications in Construction industry, shield and Lamination for air conditioning ducting system in HVAC for duct sealing of pipes and roof insulation.

Packing Construction

	Width	Length	Rolls/CTN	
	2"	30Yds	24	
2	3″	30Yds	16	
	4"	30Yds	12	

